



TRUSTED TECHNOLOGY
FOR MODERN FAXING



FAXedge FX Series

Secure Analog Fax ATAs

Experience a modern, reliable, and cost-effective solution for your faxing needs with the FAXedge FX Series Secure Analog Fax ATAs. Simplify your transition to enhanced faxing capabilities, including both physical and e-faxing on a single number with full history visibility.

Beyond providing easy migration support and a 'cap-and-grow' strategy for partners, FaxEdge offers transparent pricing with no per-page pricing, a super modern and intuitive interface, and a platform that is fully certified, PCI, and HIPAA compliant.

With geo-redundant infrastructure ensuring automatic failover and recovery, the FAXedge FX Series Secure Analog Fax ATAs deliver proven reliability for your critical communications, whether they are on-premises MFPs or in the cloud.

Key Features



PoE (Power over Ethernet) WAN Port



T.38 and G.711 Fax Protocol Support



Cloud-Based Management



Zero-Touch Provisioning (ZTP)



HIPAA Compliant



Online Monitoring Capabilities



Secures HTTPS Connectivity



Pass-Through Ethernet Port



Supports Virtual LAN (VLAN)

FAXedge Services



Web Fax

Fax through your browser with full visibility and control.



Email Fax

Send and receive faxes from your inbox.



Analog Fax

Reliably connect your analog fax machine.



Technical Specifications:

Available Hardware Configurations

Model ATA	WAN / LAN	Ports
FX-02P	10/100 Mbps	2
FX-04P	10/100 Mbps	4

Environmental & Physical Specifications

Ethernet WAN	1 X 10/100 Ethernet port WAN with PoE power in		
Optional Data Routing and Security	IPv4, DHCP client, Ability to pass through the Network, VLAN		
Physical Interfaces	Capacity: 2/4 FXS with RJ11 Ethernet Interfaces: 1 x LAN, 10/100Mbps, RJ45, 1 x WAN, 10/100Mbps, RJ45		
Management and Configuration	Cloud Provisioning	Web Configuration Interface	Cloud Firmware Upgrade
Physical Specifications <ul style="list-style-type: none"> • Weight • Dimensions • Power Supply • Max Power Consumption • Operating Temperature • Storage Temperature • Ring Load • Certification 	FX-02P 160g 125mm*85mm*28.7mm 6W 12V 1A 0°C ~ 50°C 10% ~ 90% (Non-Condensing) 2 REN, up to 3km on 24AWG line CE	FX-04P 176g 150mm*100mm*28.7mm 8W 12V 1A 0°C ~ 50°C 10% ~ 90% (Non-Condensing) 2 REN, up to 3km on 24AWG line CE	
FAXedge FX-02P/04P Contents	✓ Power supply (12V DC / 1A) ✓ Ethernet cord (1 m)		

